


## LA-97B PP anti-tamper UHF RFID tag

## Introduction



- Based on independent intellectual property development, adapt tag to work with global frequency range
- Ultra-high read rate, high sensitivity of tag identification
- Good performance of Anti-counterfeiting, transfer tamper proof, UV ultraviolet resistance design
- Application: Widely used in manufacture and logistic supply chain, digital inventory, retail, fixed asset management, items anti-counterfeit and traceability. Products look, dimension, printing could be customized. Disposable, Prevent Heat Transfer, Chemical transfer, Knife transfer, Anti-UV, No residual of removal, support indoor & outdoor application

## Specification

Specification	
Model No	LA-97B
Performance Index	
Protocol	EPC CLASS1 Gen 2 / ISO 18000-6C
Chip	ALIEN Higgs3
Working frequency	860—960MHZ
Storage capacity	TID: 96bit EPC: 128bit User: 128bit Reserve: 32bit access Password and
	32bit kill password
Dimension	110*40mm(or custom)
Work mode	Read and write
Reading times	>100,000 times
Working temperature	-25℃~+75℃
Storage temperature	0℃~25℃
Material	PP
Substrate base	Polyester Film
Antenna	Aluminum etching
Surface	Waterproof PET
Appearance characteristics	Transparent, or single or double side color printing
Product features	Disposable, Prevent Heat Transfer, Chemical transfer, Knife transfer, Anti-UV,
	No residual of removal, support indoor & outdoor application
Package	Anti-static PE + Foam stuff + Anti-static Bag

More information, welcome to visit

http://www.vanch.net/

Shenzhen Vanch Intelligent Technology Co., Ltd

TEL: 0755-8242 6775 FAX: 0755-8240 3457

Email: andy@vanch.net

